

Access Point

Porcelain Stone[®]



Available Colors



WBT01 ▶ Travertine White



WBT04 ▶ Travertine Sand



WBT05 ▶ Travertine Dove



WBT06 ▶ Travertine Ash



WBC01 ▶ Concrete White




WBC04 ▶ Concrete Sand



WBC05 ▶ Concrete Dove



WBC06 ▶ Concrete Ash



WBS01 ▶ Statuario


Features and Benefits

- Get immediate access to great design with Access Point, Crossville's collection of always-on-point and in-stock genuine porcelain tiles
- Featuring some of today's most sought-after looks – including Concrete, Statuario, and white marble visuals
- Access Point is perfect for price-conscious projects and those seeking made in the USA products
- All Access Point tiles are calibrated in 12x24 and are balanced with 2x2 mosaics and 4x24 bullnose pieces all manufactured in Crossville, TN

Access Point

Porcelain Stone[®]

Sizes *Available in all colors*



2 x 2 Square Mosaic
(Mounted on a
12 x 12 sheet)

Sizes & Finishes

Field Tile - Calibrated

Available in all colors

Nominal (in)	Actual (in)	Thickness (mm)	Grout Joint (in)	Finish
12 x 24	11-13/16 x 23-13/16	8.5	3/16	UPS

Note: Field tile is calibrated with a 3/16 inch grout joint

Mosaics

Available in all colors

Nominal (in)	Sheet Size (in)	Thickness (mm)	Grout Joint (in)	Finish
2 x 2 Mosaic*	11-15/16 x 11-15/16	8.5	3/16	UPS

* Mounted on a 12 x 12 sheet

Coordinating Trim

Available in all colors

Nominal (in)	Actual (in)	Thickness (mm)	Grout Joint (in)	Finish
4 x 24 Single Bullnose	3-13/16 x 23-13/16	8.5	3/16	UPS



4 x 24 Single Bullnose

Product Performance

Breaking Strength	>400 lbf	ASTM C648
Bond Strength	>200 psi	ASTM C482
Facial Dimension	± 0.15%	ASTM C499
Range of Thickness	0.025"	ASTM C499
Warpage	± 0.20%	ASTM C485
Wedging	± 0.30%	ASTM C502
Chemical Resistance	Unaffected	ASTM C650
Frost Resistance	Resistant	ASTM C1026
Water Absorption	<0.50%	ASTM C373
Scratch Hardness	7	Mohs Scale

Wet Dynamic Coefficient of Friction Range

UPS	0.42-0.52	ANSI A326.3
-----	-----------	-------------

Get Planked!

Our Porcelain Stone[®] products are available in popular plank shapes with no minimum order and quick fulfillment. See website for more details and sizes.



Shade & Texture Index

Access Point Concrete and Statuario has a shade variation of V2.
Access Point Travertine has a shade variation of V3.

V1	V2	V3	V4	
				V1 Uniform appearance V2 Slight Variation V3 Moderate Variation V4 Substantial Variation

This porcelain tile product is produced with a V2 variation. Expect that the amount of color and texture on each piece may vary slightly. Inspect the product upon delivery and for best results, blend tile from several cartons during installation.



Access Point

Crossville, Inc.

PO Box 1168
Crossville, TN
38557

Phone 931.484.2110
Fax 931.456.2956
E-Mail Crossc@CrossvilleInc.com
Web CrossvilleInc.com

Application Areas

Finish	Interior Floors (dry)	Interior Walls (wet/dry)	Exterior Walls	Interior Floors (Standing water/shower floors)	Exterior/Paving	Pool/Fountain Full Lining**	Water Line Pool/Fountains
UPS	✓	✓*	✓			✓	✓

* The 2 x 12 mosaic can be used in linear drain shower pans as long as the 12 inch side runs parallel to the drain.

** Excludes mesh mounted mosaics. Crossville recommends face mounted or edge mounted mosaics for fully submerged applications. Contact your Crossville sales representative for more information.

NOTE: Trim applications will differ from field tile applications for the same series.

For more information on ANSI- A362.3 visit our website at <https://www.crossvilleinc.com/Resources/Tile-101/DCOF?tab=1>

Recommended Use

Access Point is recommended for interior floors, interior walls, countertops, exterior walls, pool waterlines and full linings† in both residential and commercial applications. Access Point is not recommended for exterior horizontal surfaces or exterior paving. The Mixed Hex Mosaics and the 2 x 12 Deco pieces are to be used on interior walls only. See CrossvilleInc.com for detailed installation instructions.

† Excludes mesh mounted mosaics.

Wet area use for Access Point Mosaics

Crossville® produces the Access Point 2 x 2 mosaics with the Cross-Sheen (UPS) finish. The ANSI A326.3 wet Dynamic COF of Access Point is ≥ 0.42 . Their small sizes ensure frequent grout joints which provides traction and drainage. Crossville cannot control situations involving incorrect installation, improper slope to the drain for elimination of standing water and poor surface cleaning. This information is provided so that customers may make a realistic and informed decision when comparing Access Point to other tile products in wet area environments, such as residential/commercial bathrooms, showers, and interior pool decks.

Care and Maintenance

Regular cleaning is the best way to keep Access Point tile looking good for years to come. Use clean, hot water (combined with a household cleaner for more aggressive cleaning). Rinse thoroughly and dry with a soft cloth. No waxes are needed. More information regarding the care and maintenance of Crossville® products is available at CrossvilleInc.com.

Our Warranty

Crossville Inc. guarantees that its products will meet or exceed the performance specifications outlined in ANSI A137.1 and in the performance data section of the Crossville, Inc. general product catalog. For complete details check our website at CrossvilleInc.com.

Information listed here is subject to change. Please refer to CrossvilleInc.com for the latest, most accurate information.

▶▶ Crossville® Sample Express

Visit the website to learn more:
CrossvilleInc.com/Products/Access-Point

Loose Tile Samples

Sizes may vary depending on product series
Max. of 4 large field tile per order

Standard Shipping

FedEx Ground

CrossvilleInc.com

If you want a better idea of what Crossville tile would look like in a particular room setting, simply visit our website and click on Cross-Vision. This powerful software tool allows you to visualize different types of Crossville tile. In addition, you'll find comprehensive information about Crossville's entire portfolio of products. You can also learn about the latest styles and trends from industry experts, download detailed care and maintenance instructions for our various products, or browse electronic versions of Crossville's product brochures. So whether you need information about Crossville products or tile in general, please visit us at CrossvilleInc.com. Information listed here is subject to change.

Trade Organizations



Environmentally Aware

